

S.No.	Description of item	Qty	Unit	Rate	Amount
1	Dismantling tile work in floors and roofs laid in cement mortar including stacking material within 50 metres lead. For thickness of tiles 10 mm to 25 mm	1	Sqm		
2	Providing and fixing G.I. Pipes complete with G.I. fittings and clamps i/c making good the walls etc. concealed pipe including painting with anticorrosive bitumastic paint, cutting chases and making good the wall :15 mm dia nominal bore	3	m		
3.a	Providing and fixing G.I. Union in existing G.I. pipe line, cutting and threading the pipe and making long screws including excavation, refilling the earth or cutting of wall and making good the same complete wherever required : 15 mm nominal bore.	2	No.		
3.b	32 mm nominal bore.	3	No.		
4	Providing and fixing gun metal gate valve with C.I. wheel of approved quality (screwed end) : 32 mm nominal bore.	3	No.		
5	Providing and placing on terrace (at all floor levels) polyethylene water storage tank ISI : 12701 marked with cover and suitable locking arrangement and making necessary holes for inlet, outlet and overflow pipes but without fittings and the base support for tank	1000	Ltr		
6	Providing and fixing ball valve (brass) of approved quality, High or low pressure, with plastic floats complete : 25 mm nominal bore	2	No.		
7	Providing and fixing 3 layer PP-R (Poly propylene Random copolymer) pipes U V stabilized & anti - microbial fusion welded, having thermal stability for hot & cold water supply including all PP -R plain & brass threaded polypropylene random fittings including trenching ,refilling & testing of joints complete as per direction of Engineer in Charge. External work :PN - 16 Pipe, 32 mm OD (SDR – 7.4)	62	m		
8	Providing and fixing PTMT urinal cock of approved quality and colour. 15 mm nominal bore, 80mm long. 42 mm high and 30mm wide with BSP female threads weighing not less than 48gms.	1	No.		
9	Providing and fixing Ist quality ceramic glazed wall tiles conforming to IS : 15622 (thickness to be specified by the manufacturer) of approved make in all colours, shades except burgundy, bottle green, black of any size as approved by Engineer-in-Charge, in skirting, risers of steps and dados over 12 mm thick bed of cement Mortar 1:3 (1 cement : 3 coarse sand) and jointing with grey cement slurry @ 3.3kg per sqm including pointing in white cement mixed with pigment of matching shade complete.	1	Sqm		
10	Removing dry or oil bound distemper, water proofing cement paint and the like by scrapping, sand papering and preparing the surface smooth including necessary repairs to scratches etc. complete.	20	Sqm		
11	Providing and applying plaster of paris putty of 2 mm thickness over plastered surface to prepare the surface even and smooth complete.	20	Sqm		
12	Distempering with oil bound washable distemper of approved brand and manufacture to give an even shade :New work (two or more coats) over and including water thinnable priming coat with cement primer.	20	Sqm		
13	Providing and Fixing of Vertical blinds of approved brand and of required colour and shade including all necessary fittings like louvers, rods etc. complete in all respects as per direction of Sec/DSC and Engineer-in-charge.	8	Sqm		
				Total	